

# Miele

## PDR 507[EL MAR] Vented dryer, electrically heated Lloyd's Register approved, load size 7.0 kg.

- Drum volume 130.00L, load size 7.0 kg
- Tested for intensive use-unparalleled Miele quality
- Language-neutral fascia panel with rotary control-M Select
- Precision drying of all fabrics-PerfectDry



|                                                                                                        |                              |
|--------------------------------------------------------------------------------------------------------|------------------------------|
| Construction type and design                                                                           |                              |
| Construction type                                                                                      | Front-loader, stackable      |
| Range                                                                                                  | Performance                  |
| Front                                                                                                  | Lotus white                  |
| Fascia color                                                                                           | Stainless steel              |
| Load [kg]                                                                                              | 7.0                          |
| Drum volume [L]                                                                                        | 130.00                       |
| Drying system                                                                                          | Exhaust air                  |
| Door opening[ø mm]                                                                                     | 370                          |
| Door opening angle [°]                                                                                 | 167                          |
| Door hinge                                                                                             | left                         |
| Stainless steel honeycomb drum                                                                         | Yes                          |
| Application                                                                                            |                              |
| Suitable for offshore use                                                                              | ●                            |
| Suitable for marine use                                                                                | ●                            |
| Performance data                                                                                       |                              |
| Maximum evaporation capacity [L/hour]                                                                  | 4.40                         |
| Specific energy consumption [kWh/kg]                                                                   | 0.50                         |
| Specific energy consumption for Cottons/Normal drying programme with residual moisture at 48% [kW]     | 0.50                         |
| Specific energy consumption for mixed fibre fabrics/Normal drying programme with residual moisture [A] | 0.42                         |
| Programme duration [min]                                                                               | 46                           |
| Programme duration for Cottons/Normal drying programme with residual moisture at 48% [min]             | 46                           |
| Programme duration for mixed fibre fabrics/Normal drying programme with residual moisture at 40% [min] | 41                           |
| Controls                                                                                               |                              |
| Control system                                                                                         | M Select                     |
| Programmability                                                                                        | Programmable                 |
| User interface                                                                                         | Residual moisture controlled |
| Max.delay start [h]                                                                                    | 24                           |
| Time left display                                                                                      | ●                            |
| Programme sequence indicator                                                                           | ●                            |
| Control panel with easy-to-understand symbols                                                          | ●                            |
| Language can be selected easily at any time                                                            | ●                            |

|                                                |                   |
|------------------------------------------------|-------------------|
| Standard electrical connection                 |                   |
| Heating type                                   | Electric          |
| Electrical connection                          | 3~440V 50/60Hz    |
| Electric heater rating [kW]                    | 5.16              |
| Total connected load [kW]                      | 5.40              |
| Fuse rating [A]                                | 10                |
| Possible voltage variant 1                     |                   |
| Electrical connection                          | 3~400V 50/60Hz    |
| Heater rating [kW]                             | 4.26              |
| Total connected load [kW]                      | 4.50              |
| Fuse rating [A]                                | 10                |
| Possible voltage variant 2                     |                   |
| Electrical connection                          | 3~480V 50/60Hz    |
| Heater rating [kW]                             | 6.14              |
| Total connection load [kW]                     | 6.40              |
| Fuse rating [A]                                | 10                |
| Dimensions and weight                          |                   |
| External dimensions,height [mm]                | 850               |
| External dimensions,width [mm]                 | 596               |
| External dimensions,depth [mm]                 | 717               |
| External dimensions,gross height [mm]          | 940               |
| External dimensions,gross width [mm]           | 660               |
| External dimensions,gross depth [mm]           | 820               |
| Net weight [kg]                                | 49.0              |
| Gross weight [kg]                              | 55                |
| Maximum floor loading [N]                      | 920               |
| Emissions data                                 |                   |
| Emission sound pressure level in the workplace | <70dB(A)re 20 µPa |
| Heat dissipation into the room [MJ/h]          | 0.76              |
| Features                                       |                   |
| Intelligent drum reversal                      | ●                 |
| Axial airflow                                  | ●                 |
| Large-surface filter                           | ●                 |
| PerfectDry                                     | ●                 |
| SoftLift drum ribs                             | ●                 |
| Low temperature function                       | ●                 |
| Communication slot                             | ●                 |
| Drying basket (optional)                       | ●                 |
| Drum lighting                                  | ●                 |
| Machine-independent accessories                | ●                 |
| Connection options                             |                   |
| Payment system (optional)                      | ●                 |
| Optical interface for service access           | ●                 |
| Peak load cut-out/energy management (optional) | ●                 |
| LAN/WiFi module (optional)                     | ●                 |