

Miele

Professional Laundry PWM 907

PERFORMANCE PLUS


Construction type and version

Construction type	Front-loader,stackable	•
Front		Stainless steel
Load in kg		7.0
Drum volume in L		64
Door opening [Ø] in mm		300
Door opening angle in degrees		167
Door hinge		Right
Maintenance-free synchronous motor		Sophisticated synchronous motor
For maximum service life:The powerful,quiet and maintenance-free synchronous motor.		•
Honeycomb drum with perforated drum rear panel		•

Performance data

Specific water consumption for cold-water connection in L/kg	7.00
Specific energy consumption for cold-water connection in kWh/kg	0.14
Specific water consumption for hot water connection in L/kg	6.66
Specific energy consumption for hot water connection in kWh/kg	0.06
Water consumption with cold water connection in L	49.0
Energy consumption with cold water connection in kWh	0.98
Programme duration in minutes with cold water connection in min	59
Water consumption with hot water connection in L	46.0
Energy consumption with hot water connection in kWh	0.44
Programme duration in minutes with cold water and hot water connection in min	49
Residual moisture with cold rinse in %	48
Residual moisture with hot rinse in %	45
Spin speed in rpm	1600
G factor	704
Tested operating hours	30000

Standard electrical connection

Heating type	Electrical	•
Electrical connection		2N~400V 50-60HZ
Heater rating in kW		5.30
Total connected load in kW		5.50
Fuse rating in A		16

Dimensions and weight

External dimensions,net height in mm	850
External dimensions,net width in mm	596
External dimensions,net depth in mm	714
External dimensions,gross height in mm	940
External dimensions,gross width in mm	660
External dimensions,gross depth in mm	768
Net weight in kg	101
Gross weight in kg	105
Maximum floor loading in N	2820